



DONGGUAN JIUSHENG MACHINERY CO., LTD.

271, RENZHOU RD, DONGGUAN, GUANGDONG, CHINA

<http://www.dgchiller.com>; Email:cnjiusheng@dgchiller.com

WhatsApp:+86 158-1820-1390

Water/Oil Heater Mold Temperature Controller

Model	Unit	(water) JSSW-06	(water) JSSW-09	(water) JSSW-12	(water) JSSW-18	(water) JSSW-24	(water) JSSW-36
	Unit	(oil) JSYW-06	(oil) JSYW-09	(oil) JSYW-12	(oil) JSYW-18	(oil) JSYW-24	(oil) JSYW-36
Temperature control range	°C	water: ±30°C—120°C/±20°C—180°C, oil: ±30°C—180°C/±30°C—350°C					
Temperature control accuracy		PID±1°C					
power supply		AC 5φ 3PH-380V-50HZ					
Heat transfer media		WATER/Thermal oil					
cooling method		Direct cooling / Indirect cooling					
heating power	KW	6	9	12	18	24	36
Pump horsepower	HP	0.5	0.5 / 1	1	1	2	3
Pump working flow	L/MIN	42	42 / 56	56	56	110	315
Pump working pressure	KG/CM ²	0.5	0.5 / 1.0	1	1	1.5	2.5
Maximum power consumption	KW	1.5	1.5 / 4	4	5	11	18
Alarm function		Phase loss/water shortage/over temperature/overload/reverse/high pressure					
Cooling water piping	INCH	½	½	½	½	½	½
Circulating oil piping	INCH	3/8 x 2	3/8 x 3	3/8 x 4	3/8 x 4	3/8 x 4	1-½
Dimensions	MM	680x330x570	680x330x570	760x390x580	760x390x580	910x510x710	910x510x710
weight	KG	60	65	160	170	180	210